



## HOSE REELS FOR OIL

### AUTO SPRING HOSE REELS



#### STANDARD AUTOMATIC SPRING HOSE REEL: FLX-9016

**Standard Duty** painted steel hose reel including ½" hose 160 Bar

Part with Hose	Length (m)	Weight
FLX-9016-28708	8	18kg
FLX-9016-28710	10	18kg
FLX-9016-28715	15	20kg
FLX-9016-28720	20	27kg

OPTIONAL SWIVEL BRACKET PRODUCT # 9767



#### ADJUSTABLE ARM AUTOMATIC SPRING HOSE REEL: 9090

**Standard Duty** painted steel hose reel including ½" hose 160 Bar and adjustable arms

Part with Hose	Length (m)	Weight
FLX-9090-28708	8	18kg
FLX-9090-28710	10	18kg
FLX-9090-28715	15	20kg
FLX-9090-28720	20	27kg
FLX-9090-28725	25	32kg

OPTIONAL SWIVEL BRACKET PRODUCT # 9767



### ENCLOSED AUTOMATIC SPRING HOSE REEL: 9013

**Standard Duty** enclosed hose reel including ½" hose 160 Bar and adjustable arms

Part with Hose	Length (m)	Weight
FLX-9013-28708	8	31kg
FLX-9013-28710	10	31kg
FLX-9013-28715	15	33kg
FLX-9023-28720	20	36kg



### ADJUSTABLE ARM AUTOMATIC SPRING HOSE REEL: FLX-9065

**Heavy Duty** painted steel hose reel with twin spring and adjustable arms. Suitable for hoses of max 20m length in 1". Includes extended 5-year warranty.

**Part without Hose: FLX-9065**

**Part with Hose: FLX-9065-4885XX**

Hose is 1" dia SAE 100 R2AT 2 steel wire braided to 165bar

*Replace XX with required length of hose. Example 488515 for 15 meters*

**FOR OPTIONAL SPRING BRAKE INCLUDED. USE PRODUCT # FLX- 9065/HB**

---

## CONTROL GUNS & METERS FOR OIL



### "OIL BIT PLUS" SERIES CONTROL GUN & ELECTRONIC FLOW METER: FLX-2826

Features the following:

- Electronic oval gear flow meter
- Control gun with rubber protection guard, trigger guard, rigid outlet, automatic anti-drip nozzle and inlet swivel.

Connection	Max flow l/min	Pressure Bar	Weight
½" BSP(M)	30	70	1.5kg

**OPTIONAL ENGINE COOLANT PRODUCT # FLX-2830**

---



#### **“OIL GATE” SERIES CONTROL GUN & ELECTRONIC FLOW METER: FLX-2937**

Features the following:

- Pre-set function allows only predetermined volume of oil to be dispensed
- Electronic oval gear flow meter with pre-set
- Control gun with rubber protection guard, trigger guard, rigid outlet, automatic anti-drip nozzle and inlet swivel.

Connection	Max flow l/min	Pressure Bar	Weight
½" BSP(F)	30	70	1.6kg

#### **OPTIONAL ENGINE COOLANT PRODUCT # FLX-2942**



#### **“OIL HIFLOW” SERIES CONTROL GUN & ELECTRONIC FLOW METER: FLX-2854**

Features the following:

- Electronic oval gear flow meter with high flow rate capacity
- Control gun with rubber protection guard, trigger guard, rigid outlet, automatic anti-drip nozzle and inlet swivel.

Connection	Max flow l/min	Pressure Bar	Weight
1" BSP(M)	70	70	3.9kg



#### **ELECTRONIC OVAL GEAR FLOW METER: FLX-2829**

Suitable for in-line applications, connections 1/2" BSP.

##### **Technical Data**

Connections	<b>1/2"</b>
Flow range (l/min)	<b>1 - 30</b>
Operating temperature range	<b>min. + 10°C max. + 50°C</b>
Max. working pressure (bar)	<b>70</b>
Accuracy	<b>+/- 0,5%</b>
Total max. resettable	<b>9999 l</b>
Total max. non-resettable	<b>9999 l</b>
Weight	<b>1,5 Kg</b>