



HOSE REELS FOR GREASE

AUTO SPRING HOSE REELS



ENCLOSED AUTOMATIC SPRING HOSE REEL: FLX-9013

Standard Duty enclosed hose reel including 1/4" hose 400 Bar

FLX-9013 (Reel Only - No Hose)

Part with Hose	Length (m)	Weight
FLX-9013-4510	10	20kg
FLX-9013-4515	15	23kg

OPTIONAL SWIVEL BRACKET PRODUCT # FLX-9778



ADJUSTABLE ARM AUTOMATIC SPRING HOSE REEL: FLX-9090

Standard Duty painted steel hose reel including 1/4" hose 400 Bar and adjustable arms.

FLX-9090 (Reel Only No Hose)

Part with Hose	Length (m)	Hose	Weight
FLX-9090-4510	10	1/4"	20kg
FLX-9090-4710	10	3/8"	20kg
FLX-9090-4810	10	1/2"	22kg

OPTIONAL SWIVEL BRACKET PRODUCT FLX-9767



ADJUSTABLE ARM AUTOMATIC SPRING HOSE REEL: FLX-9091

Standard Duty painted steel hose reel including 1/4" hose 400 Bar and adjustable arms.

FLX-9091 (Reel Only No Hose)

Part with Hose	Length (m)	Hose	Weight
FLX-9090-4510	15	1/4"	25kg
FLX-9090-4520	20	1/4"	26kg

OPTIONAL SWIVEL BRACKET PRODUCT FLX-9767

CONTROL GUNS & METERS FOR GREASE



FLEXIBLE GREASE CONTROL GUN: FLX-4205

High pressure grease control gun with 300 mm steel braid rubber outlet hose $\varnothing 10$ mm and 4 jaw hydraulic coupler.

WITH TRIGGER GUARD FLX-4206



RIGID GREASE CONTROL GUN: FLX-4207

High pressure grease control gun with rigid outlet pipe and 4 jaw hydraulic coupler.

WITH TRIGGER GUARD FLX-4208



GREASE CONTROL GUN & ELECTRONIC FLOW METER: FLX-4286

Features the following:

- Digital oval gears grease flow meter
- Grease control gun with rigid outlet pipe
- Hydraulic 4 jaw coupler.
- The calibration of the meter can be made by the user.
- Equipped with 2 batteries of 1,5 V.

Connection	Max flow l/min	Pressure Bar	Weight
1/4" BSP(M)	0.2-2.0kg/min	400	1.4kg



GREASE CONTROL GUN WITH PRESET CONTROL: FLX-4236

Features the following:

- Digital oval gears grease flow meter
- Grease control gun with rigid outlet pipe
- Hydraulic 4 jaw coupler.
- The calibration of the meter can be made by the user.
- Equipped with 2 batteries of 1,5 V.
- Grease PreSet Function
 - The preselection function introduces a certain degree of automation since it becomes possible to predetermine the dosages and to stop the grease flow automatically once the preselected value has been reached.

Connection Bar	Max flow l/min	Pressure	Weight
1/4" BSP(M)	0.1-300		
2.0kg/min		1.7kg	



DIGITAL FLOW METER: FLX-4289

Features the following:

- Digital oval gears grease flow meter
- The calibration of the meter can be made by the user.
- Equipped with 2 batteries of 1,5 V.

Connection	Max flow l/min	Pressure Bar	Weight
1/4" BSP(M)	0.2-2.0kg/min	400	1.2kg